






Power relay



Control relay



**Miniature industrial relays
Classic line**



2- and 4-pole miniature industrial relays

- Push Pull-button
- Mechanical status indication (F)
- Diode/LED (Option)



Connection No. on socket →
Designation according to DIN/EN 50011

Connection with socket
EDL-14

μ = contact gap < 3 mm


Data at Tamb. = 20°C

- Contact material
Switching power AC1/DC1
Inrush current
Switching cycles mech./electr. (AC1)
- Operating voltage AC/50 Hz/DC
Power consumption AC/DC
ON delay / release time
- Operating temperature
Isolation contact/coil
Isolation contact/contact
Shock/vibration // working cond.

E42F...

Universal power relay 10A (12A)
with 2 changeover contacts for AC and DC circuits ranging from 10mA 24V.

10A (*12A) 250V~
10mA 24V




AgCdO
2500VA/...400W
20A(4 sec)
2x10⁷/≥10⁵
0,8...1,3xUn
1,2VA/0,9W
12msec/10msec no fwd
-25°C...+60°C (*+50°C)
2k Vrms 1min
1k Vrms 1min
20g/3g 10...55Hz


E45F...

Universal control relay 5A
with 4 changeover contacts for AC and DC circuits ranging from 10mA 12V.

5A 250V~
10mA 12V



AgNi
1250VA/...200W
10A(4 sec)
20x10⁷/≥10⁵
0,8...1,3xUn
1,2VA/0,9W
12msec/10msec no fwd
-25°C...+60°C
2k Vrms 1min
1k Vrms 1min
20g/3g 10...55Hz



Option:
L = ⊗
DL = ⊗ + †

G = contact AgNi + <5μm Au

24, 48, 115, 230
E42F **L** / AC ... V

12, 24, 48, 110
E42F **DL** / DC ... V

Option

24, 48, 115, 230
E45F **L** / AC ... V

12, 24, 48, 110
E45F **DL** / DC ... V

24, 48, 110
E45FGDL / DC ... V

Option



Kühn Controls S.L.
Vertriebsbüro Deutschland
Gräfenhäuser Str. 14
D-75305 Neuenbürg
Tel.: +49- (0)7082-940000
Fax: +49- (0)7082-940001
eMail: sales@kuehn-controls.de
www.multicomat.net

Ordering example

- Relay E42F/AC230V
- Socket EDL-14

Socket EDL-14

